



Color Stabiliser

transparent

250 ml - 500 ml

For all BIOFA oil-based systems on light-coloured substrates

- **Full list of ingredients**
- **Preserves the light colour of the wood surface**
- **reduces yellowing**

Features:

Colour stabiliser is a transparent, natural-based stabiliser. It is suitable for all BIOFA oil systems on light-coloured substrates. It helps light-coloured surfaces retain their light colour to a large extent by reducing the natural yellowing of the oils and resins.

Ingredients:

Aromatics-free, highly purified test petrol, titanium dioxide, swelling clay, wetting agent, defoamer.

0 per cent water and renewable raw materials

12 per cent mineral and metallic raw materials

88 per cent chemical-synthetic and fossil raw material

Usage:

The Color stabiliser must be stirred thoroughly and mixed homogeneously into the relevant BIOFA oil at a concentration of up to 5% by weight (up to 10% for rock oil) prior to application.

Give the oil a good stir every now and then. You should always carry out a test run first.

Please note! Ensure there is adequate fresh air circulation during the application and drying of the products!

Cleaning of tools:

Clean immediately after use with BIOFA Thinner 0500.

Storage:

Store in a cool, dry place and keep tightly sealed.

Disposal:

Dispose of any remaining liquid product and any containers that have not been completely emptied and cleaned at a collection point for waste paints and varnishes, or dispose of them in accordance with the relevant local or national legal regulations. Small residual quantities and soaked work materials can be disposed of with household waste once they have dried out. Only put completely empty and clean containers out for recycling.

AVV waste code according to the European Waste Catalogue: 08 01 11*

Safety instructions:

Warning! Spraying may produce dangerous respirable droplets. Do not breathe in the aerosol or mist. Repeated exposure may cause skin to become rough or cracked. Keep out of the reach of children. If medical advice is needed, have the container or label at hand. Avoid contact with eyes, skin or clothing. Ensure adequate skin protection. **IF ON SKIN:** Wash off with plenty of soap and water. Use only outdoors or in well-ventilated areas. Do not allow to enter watercourses, drains or the ground.

Safety data sheet available on request.

2108 contains a maximum of 755 g/l VOC.

